




High Voltage Insulated Operating Rod, Telescopic

Category: Insulating Tools, Ladders & Detectors Product code: insulated-operating-rod-telescopic

Telescopic fibreglass-reinforced epoxy operating rod for live-line working and distribution line maintenance. Linked and telescopic types from 10 kV to 500 kV, with fluorescent tip, non-slip grip and locking joints.

SPECIFICATIONS

Material	Fibreglass-reinforced epoxy resin
Types	linked type / telescopic type
Voltage range	10 kV / 35 kV / 110 kV / 220 kV / 500 kV
Section count	2 / 3 / 4 / 5 sections
Working length	2 m to 10 m
Joint	locking threaded joint, anti-loosening
Grip	non-slip rubber handle
Tip	fluorescent green for night-time visibility
Surface	smooth, easy to clean
Testing	insulation withstand test on every batch
Storage	dry, ventilated place away from direct sunlight and impact
Accessory	rain cover available

STANDARDS & CERTIFICATIONS

ISO 9001 (company quality management system)

PACKAGING & DELIVERY

MOQ	5 units
Packaging	215 x 8 x 8 cm, gross weight 6.1 kg
Lead time	15 days for 1-5 units; 30 days for 6-100 units

PRODUCT VIEWS

